



1. Open/Short/Intermittence: 100%
2. Insulation Resistance: DC300V 10mS 10M Ω (Min)
3. Conductive Resistance: 5 Ω (Max)
4. RoHS & REACH COMPLIANT

Diagram of a three-wire cable with P1, P2, and P3 conductors. P1 is labeled 'SPIRAL', P2 is labeled 'WHITE', and P3 is labeled 'RED'. Each conductor has a terminal symbol at the right end.

⑥	MOLDED	45P RED PVC		G	Ltemref	Quantity	Title/Name, designation, material, dimension etc	Article NO. /Reference		
⑤	MOLDED	45P WHITE PVC		G						
④	MOLDED	45P BLACK PVC		G	Designed by FLY	Checkde by HELEN	Approved by - date 2025. 12. 04	File name	Date 2025. 12. 04	Scale FREE
③	CONNECTOR	RAC MALE, WHITE INSULATION, GOLD-PLATED BRASS	2	PCS						
②	CONNECTOR	DC3.5MM 3-POLE MALE STEREO PLUG:BRASS, GOLD-PLATED	1	PCS	ANGLE:			DC 3.5 M TO 2*RCA		
①	CABLE	[10/0.10CCS+SPIRAL(28*0.10CCS)]*2C, BLACK MATT PVC, OD:2.8*5.6±0.15mm	L	MM						
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT	UNIT:MM			23-1***	Edition 1	Sheet 1/1