


P/N	L/mm	T/mm
23-2020	2000	30
23-2030	3000	40
23-2050	5000	80
23-2100	10000	100
23-2150	15000	120
23-2200	20000	150

PIN OUT



- NOTES:
- 1. Open/Short/Intermittence: 100%
 - 2. Insulation Resistance: DC300V 10mS 10MΩ (Min)
 - 3. Conductive Resistance: 5Ω (Max)
 - 4. RoHS & REACH COMPLIANT

					Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference		
					Designed by FLY		Checkde by HELEN		Approved by - date 2025. 12. 04	File name	Date 2025. 12. 04	Scale FREE
③	MOLDED	45P BLACK PVC		G	ANGLE:					DC3.5 M TO M		
②	CONNECTOR	DC3.5MM 3-POLE MALE STEREO PLUG:BRASS, GOLD-PLATED	2	PCS								
①	CABLE	10/0.10CCS*2C+D(10/0.10CCS)+BLACK MATT PVC JACKET, OD:3.0±0.15mm	L	MM	UNIT:MM							
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT						23-2***	Edition 1	Sheet 1/1