



P/N	L/mm	T/mm
23-3020	2000	30
23-3030	3000	40
23-3150	15000	150

PIN OUT

Diagram illustrating three parallel horizontal lines connecting two points, P1 and P2. The lines are labeled 1, 2, and 3 at both ends.

NOTES:

1. Open/Short/Intermittence: 100%
2. Insulation Resistance: DC300V 10mS 10M Ω (Min)
3. Conductive Resistance: 5 Ω (Max)
4. RoHS & REACH COMPLIANT

					Ltemref	Quantity	Title/Name, designation, material, dimension etc	Article NO. /Reference			
					Designed by FLY		Checkde by HELEN	Approved by - date 2025. 12. 04	File name	Date 2025. 12. 04	Scale FREE
③	MOLDED	BLACK PVC		G	ANGLE:		RCA M TO M				
②	CONNECTOR	RAC MALE, WHITE INSULATION, PLUG: BRASS, GOLD-PLATED	2	PCS							
①	CABLE	10/0. 10CCS+D(10/0. 10CCS), BLACK MATT PVC, OD: 3. 0±0. 15mm	L	MM	UNIT:MM		23-3*** Edition 1 Sheet 1/1				
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT							