


P/N	L/mm	T/mm
23-5020	2000	30
23-5030	3000	45
23-5050	5000	60
23-5100	10000	100

PIN OUT



- NOTES:
- 1. Open/Short/Intermittence: 100%
 - 2. Insulation Resistance: DC300V 10mS 10M Ω (Min)
 - 3. Conductive Resistance: 5 Ω (Max)
 - 4. RoHS & REACH COMPLIANT

					Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO. /Reference			
④	MOLDED	45P BLACK PVC		G	Designed by FLY	Checkde by HELEN	Approved by - date 2025. 12. 04		File name	Date 2025. 12. 04	Scale FREE		
③	CONNECTOR	DC3. 5MM 3-POLE MALE STEREO PLUG:BRASS, GOLD-PLATED	2	PCS	ANGLE: 				DC 3.5 M TO F				
②	CONNECTOR	DC3. 5MM 3-POLE FEMALE STEREO PLUG:BRASS, GOLD-PLATED	1	PCS									
①	CABLE	10/0. 10CCS*2C+SPIRAL (28/0. 10CCS), BLACK MATT PVC JACKET, OD:4. 0±0. 15mm	L	MM	UNIT:MM								
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT							23-5***		Edition 1