



P/N	L/mm	T/mm
23-5020	2000	30
23-5030	3000	45
23-5050	5000	60
23-5100	10000	100

PIN OUT

Diagram illustrating three parallel horizontal lines connecting two points, P1 and P2. The lines are labeled 1, 2, and 3 on both ends.

NOTES:

1. Open/Short/Intermittence: 100%
2. Insulation Resistance: DC300V 10mS 10M Ω (Min)
3. Conductive Resistance: 5 Ω (Max)
4. RoHS & REACH COMPLIANT

					Ltemref	Quantity	Title/Name, designation, material, dimension etc	Article NO. /Reference		
④	MOLDED	45P BLACK PVC		G	Designed by FLY	Checkde by HELEN	Approved by - date 2025. 12. 04	File name	Date 2025. 12. 04	Scale FREE
③	CONNECTOR	DC3. 5MM 3-POLE MALE STEREO PLUG:BRASS, GOLD-PLATED	2	PCS						
②	CONNECTOR	DC3. 5MM 3-POLE FEMALE STEREO PLUG:BRASS, GOLD-PLATED	1	PCS	ANGLE: 				DC 3.5 M TO F	
①	CABLE	10/0. 10CCS*2C+SPIRAL (28/0. 10CCS), BLACK MATT PVC JACKET, OD:4. 0±0. 15mm	L	MM						
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT	UNIT:MM			23-5***	Edition 1	Sheet 1/1