



P/N	L/mm	T/mm
26-0020MF	2000	30
26-0030MF	3000	50
26-0050MF	5000	80
26-0100MF	10000	100

NOTES:

1.Open/Short/Intermittence: 100%

2.Insulation Resistance: DC300V 10mS 10MΩ(Min)

3.Conductive Resistance: 10Ω(Max)

4.RESOLUTION: 1440*900@60Hz

5.RoHS & REACH COMPLIANT

P1	P2	P1	P2
1	1	9	9
2	2	10	10
3	3	11	11
4	4	12	12
5	5	13	13
6	6	14	14
7	7	15	15
8	8	SHELL	SHELL

⑦	NUT	NICKEL-PLATED NUT	2	PCS
⑥	SCREW	4-40 UNC, NICKEL-PLATED, PVC MOLDED	4	PCS
⑤	MOLDED	45P BLACK PVC		G
④	MOLDED	LDPE		G
③	CONNECTOR	VGA 15P FEMALE, GOLD PLATED PIN,BLUE INSULATION,NICKEL PLATED SHELL	1	PCS
②	CONNECTOR	VGA 15P MALE, GOLD PLATED PIN,BLUE INSULATION,NICKEL PLATED SHELL	1	PCS
①	CABLE	[(7/0.10TC)+FPE+D(7/0.10TC)+AL+PVC]*3C+7/0.10TC*9C+AL+D(7/0.10TC)+B(16*5/0.12AL-MG) , BLACK PVC DENTATE JACKET, OD:8.0±0.2MM MARKING:connektgear AWM STYLE 2919 80℃ 30V LOW VOLTAGE Computer Cable RoHS & REACH Compliant	L	MM
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference		
Designed by FLY	Checkde by HELEN	Approved by - date 2024. 11. 28	File name	Date 2024. 11. 28	Scale FREE		
ANGLE: 			VGA(3+9)M-F 30AWG				
UNIT:MM					Edition 1	Sheet 1/1	