



P/N	L/mm	T/mm
26-0150MM	15000	100
26-0200MM	20000	120
26-0250MM	25000	150
26-0300MM	30000	150
26-0500MM	50000	200

NOTES:

1. Open/Short/Intermittence: 100%

2. Insulation Resistance: DC300V 10mS 10MΩ (Min)

3. Conductive Resistance: 10Ω (Max)

4. RESOLUTION: 1440*900@60Hz

5. RoHS & REACH COMPLIANT

P1	P2	P1	P2
1	1	9	9
2	2	10	10
3	3	11	11
4	4	12	12
5	5	13	13
6	6	14	14
7	7	15	15
8	8	SHELL	SHELL

⑥	FERRITE	φ 17.5*φ 9.5*28	2	PCS								
⑤	SCREW	4-40 UNC, NICKEL-PLATED, PVC MOLDED	2	PCS								
④	MOLDED	45P BLACK PVC		G	Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference		
③	MOLDED	LDPE		G								
②	CONNECTOR	VGA 15P MALE, GOLD PLATED PIN, BLUE INSULATION, NICKEL PLATED SHELL	2	PCS								
①	CABLE	[(7/0.12BC)+FPE+D(7/0.12BC)+AL+PVC]*3C+7/0.12BC*9C+AL+D(7/0.12BC)+B(16*5/0.12AL-MG), BLACK PVC DENTATE JACKET, OD:8.0±0.2MM MARKING:connektgear AWM STYLE 2919 80℃ 30V LOW VOLTAGE Computer Cable RoHS & REACH Compliant	L	MM								
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT	Designed by FLY	Checkde by HELEN	Approved by - date 2024.11.28	File name	Date 2024.11.28	Scale FREE		
					ANGLE: 				VGA(3+9)M-MFERRITE 28AWG			
					UNIT:MM						Edition 1	Sheet 1/1