


P/N	L/mm	T/mm
26-2850	2000	30

NOTES:

- 1. OPEN/SHORT/INTERMITTENCE:100%.
- 2. INSULATION RESISTANCE:DC 300V 0.01S 10M Ω Min
- 3. CONDUCTIVE RESISTANCE:5 Ω Max
- 4. ROHS & REACH COMPLIANT



⑤	MOLDED	45P BLACK PVC		G							
④	MOLDED	LDPE		G							
③	CONNECTOR	USB2.0 MINI 5P MALE, GOLD PLATED PIN, BLACK INSULATION, NICKEL PLATED SHELL	1	PCS	Ltemref	Quantity	Title/Name, designation, material, dimension etc		Article NO./Reference		
②	CONNECTOR	USB2.0 A MALE, GOLD PLATED PIN, WHITE INSULATION, NICKEL PLATED SHELL	1	PCS	Designed by FLY		Checkde by HELEN	Approved by - date 2025. 11. 07	File name	Date 2025. 11. 07	Scale FREE
①	CABLE	7/0.12BC*1P+7/0.12BC*2C+AL+D(7/0.12CCS)+B(48/0.12AL-MG), BLACK PVC JACKET, OD:3.8±0.2mm MARKING: connektgear AWM STYLE 2725 80°C 30V VW-1 USB2.0 HIGH SPEED CABLE ROHS & REACH COMPLIANT	2000	MM	ANGLE: 				USB2.0 AM-MINI 5P		
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT	UNIT:MM				26-2850		Edition 1