



1. OPEN/SHORT/INTERMITTENCE:100%.
2. INSULATION RESISTANCE:DC 300V 0.01S 10M Ω MIN
3. CONDUCTIVE RESISTANCE:5 Ω MAX
4. RESOLUTION:4K*2K@60HZ.
5. ROHS & REACH COMPLIANT

⑤	DUST CAP	HDMI A MALE DUST CAP	2	PCS	<table><tr><td>Ltemref</td><td>Quantity</td><td colspan="3">Title/Name, designation, material, dimension etc</td><td colspan="3">Article NO./Reference</td></tr><tr><td colspan="2">Designed by FLY</td><td>Checkde by HELEN</td><td>Approved by - date 2025. 10. 31</td><td>File name</td><td>Date 2025. 10. 31</td><td>Scale FREE</td></tr><tr><td colspan="2">ANGLE: </td><td colspan="3" rowspan="2"></td><td colspan="2">HDMI2.0 AM-AM 4K*2K@60Hz</td></tr><tr><td colspan="2">UNIT:MM</td><td colspan="2">26-70XX4K</td><td>Edition 1</td><td>Sheet 1/1</td></tr></table>	Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference			Designed by FLY		Checkde by HELEN	Approved by - date 2025. 10. 31	File name	Date 2025. 10. 31	Scale FREE	ANGLE: 					HDMI2.0 AM-AM 4K*2K@60Hz		UNIT:MM		26-70XX4K		Edition 1	Sheet 1/1
Ltemref	Quantity	Title/Name, designation, material, dimension etc				Article NO./Reference																											
Designed by FLY		Checkde by HELEN	Approved by - date 2025. 10. 31	File name		Date 2025. 10. 31	Scale FREE																										
ANGLE: 						HDMI2.0 AM-AM 4K*2K@60Hz																											
UNIT:MM						26-70XX4K		Edition 1	Sheet 1/1																								
④	MOLDED	45P BLACK PVC		G																													
③	MOLDED	LDPE		G																													
②	CONNECTOR	HDMI 19PIN MALE THE PIN GOLD PLATED, BLACK INSULATION, GOLD PLATED SHELL	2	PCS																													
①	CABLE	(1/0. 254BC*1P+1/0. 254CCS+AM)*5+1/0. 254BC*4C+AL-FOIL+D(1/0. 254BC)+B(64/0. 12AL-MG), BLACK PVC JACKET, OD:6.0±0. 2MM, MARKING: High Speed HDMI [®] Cable with Ethernet	L	MM																													
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT																													